



ZF LifeguardFluid 7.5 DCT

Transmission oil for modern double clutch transmissions with wet clutches

Product Description:

ZF LifeguardFluid 7.5 DCT is a high-quality premium performance transmission oil, specially developed for use in modern double clutch transmissions with wet clutches. It was designed to ensure outstanding performance, protection and durability in modern vehicles with double clutch transmissions.

The high-quality additive technology combines excellent wear protection properties with optimal friction coefficient behavior and thus offers the best shifting comfort even under the highest requirements.

Application:

ZF LifeguardFluid 7.5 DCT was specially developed for the application in double clutch transmissions with wet clutch and offers optimal friction characteristics that ensure precise and friction-free shifting performance. The special formulation offers effective protection against wear and extends the service life of the transmission components. The transmission oil also offers excellent temperature stability and protects the transmission from overheating, especially under demanding operating conditions.

ZF LifeguardFluid 7.5 DCT is compatible with various double clutch transmissions and meets the requirements of leading vehicle manufacturers.

The oil change intervals must be observed and carried out according to the manufacturer's instructions. The items required for an oil change can be obtained from www.zf-aftermarket.com.

Shake small containers (up to 20 l) vigorously for at least 15 s before removing the oil. Mix large containers (above 20 l) with a suitable and clean agitator (min. 1500 rpm) for at least 60 min at room temperature before removing the oil.



ZF LifeguardFluid 7.5 DCT

Transmission oil for modern double clutch transmissions
with wet clutches

Product properties:

Product no.		
5961.308.624	Bottle	1 l
Characteristics (typical values)		
Color	yellow	
Density at 15° C (ISO 12185)	840 kg/m ³	
Viscosity at 40° C (DIN 51562)	18 mm ² /s	
Viscosity at 100°C (DIN 51562)	4.4 mm ² /s	
Viscosity index (DIN ISO 2909)	185	
Pour point (ISO 3016)	-45 °C	