



ZF LifeguardFluid CVT 1

Product description:

ZF LifeguardFluid CVT 1 is a high-performance transmission oil specially developed for continuously variable transmissions. Designed for use in Continuously Variable Transmissions (CVT), this transmission oil provides outstanding performance and protection for various vehicle models.

Features and advantages:

Specially developed additive components for maximum performance and durability.

Developed for use in continuously variable transmissions (CVT) from various manufacturers.

Provides excellent lubrication and reduces wear on transmission components.

Excellent thermal stability that ensures reliable performance under extreme operating conditions.

Optimum friction properties for smooth and efficient shifting.

Protection against corrosion and oxidation to extend the service life of the transmission.

Compatible with a variety of CVT vehicles, including high-performance and standard applications.

Fields of application:

ZF LifeguardFluid CVT 1 is ideal for use in various vehicles with continuously variable transmissions, including passenger cars, SUVs, vans and other vehicles that require CVT fluids according to manufacturer's specifications.

ZF Friedrichshafen AG

Löwentaler Str. 20
88046 Friedrichshafen
Germany

Phone + 49 7541 77-0

aftermarket.zf.com

zf.com/dis

Page/Page 12< ffplaceholder



ZF LifeguardFluid CVT 1

Before use, the operating conditions and the manufacturer's specifications of the respective vehicle and transmission should be taken into account.

It is recommended to change the oil according to the maintenance intervals of the vehicle to ensure the optimal performance of the transmission.

Small containers (up to 20 l) must be shaken vigorously for at least 15 s before removing the oil. Large containers (over 20 l) must be mixed with a suitable and clean agitator (min. 1500 rpm) for at least 60 min at room temperature before taking the oil.

Product characteristics:

Product no.		
Bottle	1 litre	5961.308.626
Characteristics (typical values)		
Color	Amber yellow	
Density at 15 ° C (DIN 51757)	0.850 g/ml	
Viscosity at 40 ° C (DIN 51562-1)	35.0 mm ² /s	
Viscosity at 100 ° C (DIN 51562-1)	7.3 mm ² /s	
Viscosity index (DIN ISO 2909)	170	
Pourpoint (DIN ISO 3016)	-48 ° C	