



ZF LifeguardFluid CVT 2

Product description:

ZF LifeguardFluid CVT 2 is a high-performance transmission oil specially developed for use in continuously variable transmissions (CVT). This oil provides excellent performance and protection for CVT systems in a variety of vehicles.

Features and advantages:

Specially developed additive components for maximum performance and durability.

Developed for use in continuously variable transmissions (CVT) according to the latest requirements.

Provides excellent lubrication properties to reduce wear on transmission components.

Excellent thermal stability for reliable performance under extreme operating conditions.

Optimum friction properties over the entire change interval.

Protection against corrosion and oxidation to extend the service life of the transmission.

Meets or exceeds the requirements of leading vehicle manufacturers and industry standards.

Application:

ZF LifeguardFluid CVT 2 is ideal for use in various vehicles with continuously variable transmissions, including passenger cars, SUVs, vans and other vehicles that require CVT fluids according to manufacturer's specifications.



ZF LifeguardFluid CVT 2

Before use, the operating conditions and the manufacturer's specifications of the respective vehicle and transmission should be taken into account.

It is recommended to change the oil according to the maintenance intervals of the vehicle to ensure the optimal performance of the transmission.

Small containers (up to 20 l) must be shaken vigorously for at least 15 s before removing the oil. Large containers (over 20 l) must be mixed with a suitable and clean agitator (min. 1500 rpm) for at least 60 min at room temperature before taking the oil.

Product characteristics:

Product no.		
Bottle	1 litre	5961.308.627
Characteristics (typical values)		
Color	Amber yellow	
Density at 15 ° C (DIN 51757)	0.848 g/ml	
Viscosity at 40 ° C (DIN 51562-1)	34 mm ² /s	
Viscosity at 100 ° C (DIN 51562-1)	7 mm ² /s	
Viscosity index (DIN ISO 2909)	173	
Pourpoint (DIN ISO 3016)	-52 ° C	